


慈溪市万捷电子有限公司




CIXI WANJIE ELECTRONIC CO., LTD

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



P.C.B. LAYOUT



UL/CUL 技术参数		UL/CUL Technical Data			UL		
等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	-	300			
额定电流	Rated Current [A]	15	-	10			
接线范围	Wire Range						
单/多芯线	Solid/Stranded [AWG]						
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数		IEC Technical Data			IEC		
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	250	320	400			
额定电流	Rated Current [A]	10	10	10			
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0			
导线截面积	Conductor cross section						
硬质/柔性导线	Solid/ flexibl [mm ²]						
材料		Material					
绝缘材料	Insulation Material	PA66					
阻燃等级	Imflamability	UL94V-0					
导体材料	Contacto Material	铜合金 Copper alloy					
导体表面镀层	Contactive Coating	镀锡 Sn Plated					
一般参数		Other Data					
间距	Pitch /极数 Poles [mm] / [P]	5.08 / 02-24					
剥线长度	Stripping Length [mm]	~					
螺丝	Screw/扭矩 Torque(Max)[N.m]	-					
工作温度	Operating temperature [°C]	-40~105					
焊锡温度	Soldering temperature	260°C/5S					
引针尺寸	Pin Dimensions [mm]	1.0*1.0					
PCB板孔径	PCB Hole Diameter [mm]	Ø1.7					

linear dimension(Tolerances Standard GB/T 14486-2008)

variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	2:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						名称 / TITLE	WJ2EDGRC-5.08-XXP-1YY-00A	